

DECLARATION OF PERFORMANCE

Regulation (EU) no 305/2011

FIRESEALSIL_DOP_15651_2102

1. Unique identification code of the product-type:

FIRE SEALING SILICONE

2. Intended use/es:

EN 15651-1:2012 - Sealants for facade elements, outdoor and indoor application, for use in cold climatic areas. F-EXT/INT-CC

EN 15651-1:2012 - Sealants for facade elements, outdoor and indoor application, for use in cold climatic areas. F-EXT/INT-CC

3. Manufacturer:

ROTHO BLAAS SRL - via dell'Adige 2/1 - 39040 Cortaccia (BZ) - Italy

5. System/s of AVCP:

EN 15651-1:2012 - System 3

6a. Harmonised standard:

EN 15651-1:2012 Sealants for non-structural use in joints in buildings and pedestrian walkways | Part 1: Sealants for facade elements

EN 15651-1:2012 - Sealants for non-structural use in joints in buildings and pedestrian walkways | Part 1: Sealants for facade elements

Notified Body/ies:

EN 15651-1: MPA NRW - Materialprüfungsamt Nordrhein-Westfalen (NB 0432)

EN 15651-1: ITB - INSTYTUT TECHNIKI BUDOWLANEJ (NB 1488) (Reaction to fire)

7. Declared performance/s:

see next page

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

FIRESEALSIL_CPR_15651_2102

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Luca Sestigiani

Technical Director

Cortaccia, 02.10.2025

This document consists of pages 2

DOP_EN
Page 1 of 2

ROTHO BLAAS SRL

7. Declared performance/s:

Conditioning ISO 8339/A
 Substrate/s Aluminium (primer)

Essential characteristics	Performance/s	Harmonised technical specification
Reaction to fire	B-s2,d0 class	EN 15651-1:2012
Release of dangerous substances	see SDS	
Water tightness and air tightness :		
a) Change in mass and volume	≤ 10 %	
b) Resistance to flow	≤ 3 mm	
c) Tensile properties of sealants at maintained extension after immersion in water	npd	
d) Tensile properties (Extension to break)	≤ 0.9 N/mm ²	
Durability	pass	